



DELO[®] SYN-GEAR HD

SAE 75W-90

PRODUCT DESCRIPTION

"Delo. Let's go further.[®]"

Delo[®] Syn-Gear HD gear lubricant is a heavy duty, extreme pressure, multigrade automotive gear lubricant.

CUSTOMER BENEFITS

Delo Syn-Gear HD delivers value through:

- **Extended drain capabilities** — Field proven in fleet testing for 500,000-mile drain intervals.
- **Excellent thermal and oxidation stability** — The synthetic hydrocarbon base oil used in this product provides outstanding stability.
- **High viscosity index and low pour point** — The synthetic hydrocarbon base stock provides extremely broad operating temperature ranges when compared with conventional mineral oil based gear lubricants.
- **Excellent seal compatibility** — This product is compatible with widely used seal elastomers.
- **Refill and top off compatibility** — Delo Syn-Gear HD is compatible with conventional mineral oil based and other synthetic automotive gear lubricants.

FEATURES

Delo Syn-Gear HD is a heavy duty, extreme pressure, multigrade automotive gear lubricant.

ISOSYN
TECHNOLOGY[®]

It is manufactured from synthesized hydrocarbon base fluids which have excellent thermal and oxidation stability, a high viscosity index, and a low pour point.

The low pour point of Delo Syn-Gear HD imparts maximum lubrication during startup at subzero temperatures, while its improved viscosity-temperature characteristics provide dependable lubrication at high temperatures. Low frictional losses in the lubricant film and minimal churning losses due to lower bulk oil viscosity lead to reduced operating temperatures when compared to conventional gear lubricants.

APPLICATIONS

Delo Syn-Gear HD is recommended as a rear axle and differential lubricant in over-the-road and off-road vehicles when operating under severe conditions and in extremely cold or hot environments.

Delo Syn-Gear HD meets or exceeds the requirements of **API Service Categories** GL-4, GL-5 and MT-1. This product passed the field and bench requirements for the original version of Dana's SHAES 256 extended drain axle lubricant specification (Revision A, now obsolete). In addition, it is approved for **Volvo 97312** and **SAE J2360** (formerly MIL-PRF-2105E) and meets the requirements of:

- **Mack** GO-J
- **MAN Nutzfahrzeuge** 342 Type M2
- **Meritor** O-76 Extended Drain

This product has been successfully field tested for long drain intervals in class 8 on-highway trucks using axles made by the following OEMs: **Meritor, DAF, Daimler, Dana, MAN** and **Scania**.

Product(s) manufactured in the USA.

Always confirm that the product selected is consistent with the original equipment manufacturer's recommendation for the equipment operating conditions and customer's maintenance practices.

A **Chevron** company product

6 July 2015
GL-17

© 2014-2015 Chevron U.S.A. Inc. All rights reserved.

Chevron, the Chevron Hallmark, Delo, Delo. Let's go further., ISOSYN and the ISOSYN logo are trademarks owned by Chevron Intellectual Property LLC. All other trademarks are property of their respective owners.

TYPICAL TEST DATA

SAE Grade	75W-90
<i>Product Number</i>	223034
<i>SDS Number</i>	35588
Density at 60°F, lb/gal	7.22
Viscosity, Kinematic mm ² /s at 40°C mm ² /s at 100°C	108 15.1
Viscosity, Brookfield mPa.s at -40°C	137,500
Viscosity Index	146
Flash Point, °C(°F)	192(378)
Pour Point, °C(°F)	-45(-49)

Minor variations in product typical test data are to be expected in normal manufacturing.

Always confirm that the product selected is consistent with the original equipment manufacturer's recommendation for the equipment operating conditions and customer's maintenance practices.

6 July 2015
GL-17