



Technical Data Sheet

Shell Rotella® T3 10W-30 (CJ-4)

- Low Emissions
- Maintenance Savings

Fleet Multigrade Heavy Duty Diesel Engine Oils

Shell Rotella® T3 Energized Protection™ oils use the latest "Low-SAPS" additive technology to protect under the most severe conditions found in modern low emission engines. The protective power of the oil is enhanced through the use of high purity "Group II" base oils that provide increased additive activity.

The exclusive high TBN/low-ash formulation helps protect the exhaust catalysts and particulate traps found on the latest low emission vehicles. Recommended by a wide range of OEMs, suitable for both the latest low-emissions and older model equipment. Designed for fleet and off highway use, Shell Rotella® T3 offers the convenience of a single oil suitable for your entire fleet.



ENERGIZED PROTECTION
Adapting to your engine's changing needs

Performance, Features & Benefits

■ Simplify inventory needs

Shell Rotella® T3 is approved by a wide range of leading OEMs, simplifying inventory needs for fleets with a mixture of engine makes.

■ Emissions systems capability

Advanced low-ash formulation helps control blocking or poisoning of exhaust after-treatment devices, helping maintain vehicle emission compliance and engine fuel efficiency.

■ Lower operating costs

Shell Rotella® T3 is formulated with an enhanced acid-control system to help fleet operators to achieve maximum drain flexibility.

■ Extended drain capability

Formulated with an optimized detergent system designed to provide high TBN and extended drain capabilities, demonstrated by meeting the requirements of API CJ-4 and CI-4 PLUS.

■ Outstanding shear stability and soot control

Shell Rotella® T3 uses an additive system designed to provide outstanding viscosity control throughout the drain interval for consistent lubrication and wear protection.

Main Applications



■ Severe duty heavy duty diesel engines

Shell Rotella® T3 provides outstanding protection for virtually all heavy duty diesel engines, including engines with the latest emission controlled engines using EGR and containing a Diesel Particulate Filter.

■ Off-highway applications

Suitable for use in agricultural and construction applications, even with high levels of fuel Sulfur.

Specifications, Approvals & Recommendations

■ API: CJ-4, CI-4 PLUS, CI-4, CH-4, CG-4, CF-4, CF

■ API SM, SL

■ Caterpillar: ECF-2, ECF-3

■ For a full listing of equipment approvals and recommendations, please consult your local Shell Technical Help Desk, or the OEM Approvals website.

Typical Physical Characteristics

Properties	Method	Shell Rotella T3 10W-30
SAE Viscosity Grade	J300	10W-30
Kinematic Viscosity @40°C	mm ² /s	ASTM D445 80
Kinematic Viscosity @100°C	mm ² /s	ASTM D445 12
Viscosity Index	ASTM D2270	144
Density @15°C	kg/l	ASTM D4052 0.870

Properties		Method	Shell Rotella T3 10W-30
Sulfated Ash	%	ASTM D874	1.0
Total Base Number	mg KOH/g	ASTM D2896	10.6
Flash Point (Cleveland Open Cup)	°C	ASTM D92	227
Pour Point	°C	ASTM D97	-30

These characteristics are typical of current production. While future production will conform to Shell's specification, variations in these characteristics may occur.

Health, Safety & Environment

■ Health and Safety

Shell Rotella T3 is unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained.

Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.

Guidance on Health and Safety is available on the appropriate Material Safety Data Sheet, which can be obtained from your Shell representative.

■ Protect the Environment

Take used oil to an authorized collection point. Do not discharge into drains, soil or water.

Additional Information

■ Advice

Product recommendations for applications and specifications not covered here may be obtained from your Shell representative.