

SERVICE PRO® PREMIUM HI-TEMP EP-2 LITHIUM COMPLEX GREASE

Formulated for high temp wheel bearing applications

DESCRIPTION: SERVICE PRO® Premium High-Temp Grease is an exceptionally versatile multi-purpose grease that provides superior protection to lubricate a wide variety of severe duty automotive, trucking, industrial, mining and construction equipment. Service Pro® Premium High-Temp Grease contains extreme pressure (EP) additives to minimize wear in heavily-loaded components and is suitable for use at higher temperatures than conventional greases. This grease satisfies a wide range of industrial and automotive applications including wheel bearings, ball joints and bushings.

- PERFORMANCE BENEFITS:**
- Premium quality lithium complex multi-purpose grease
 - Fully additive treated: EP/anti-wear, rust and oxidation inhibited
 - Highly water resistant
 - Superior disc brake wheel bearing and chassis performance
 - Meets the requirements of NLGI Service Classification GC-LB

TYPICAL PROPERTIES:	NLGI Consistency Number	2
	Thickener	Lithium Complex
	Texture	Smooth, Buttery
	Color, Observed	Red
	Worked 60 Penetration, D-217	265-295
	Dropping Point, D-2265, °F. (°C.)	500 (260)
	Wheel Bearing Leakage, D-4290, g loss	2.3
	Water Washout, D-1264, % loss	1.7 @ 175°F.
	Rust Prevention, D-1743, rating	Pass
	Copper Corrosion, D-4048, rating	Pass
	Oxidation Stability, D-942, psi drop	5 @ 100 hrs
	Oil Separation, D-1742, % loss	0.8
	Timken OK Load, D-2509, lb.	45
	Four-Ball Wear, D-2266, mm	0.4
	Four-Ball EP Weld Point, D-2596, kgf	315
	Four-Ball Load Wear Index, D-2596, kgf	45
	Approximate Temperature Range, °F. (°C.).	10 to 325 (-12 to 163)